



SLIDING




CLIMBING



SECURITY AREA

1200

1000



	CATALOG COLLECTION	FUN COLLECTION
	DIMENSIONS (L x W x H) in cm	860 x 640 x 580 cm
	IMPACT AREA	77,50 m ²
	MAXIMUM CFH	150 cm
	SUGGESTED AGE OF USE	3+
	NUMBER OF USERS	35

PRODUCT SHEET

REV 0.0 - IT202504

6990 ARIEL



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
 ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
 Certificate N.: GOTT2532Q1902


ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
 ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
 Certificate No: GOTT2532E1801

COMPOSITION

- n° 30 90x90 mm square section timber or aluminum structural posts
- n° 18 decks with powder-coated metal frame and timber or aluminum slats
- n° 1 HDPE sheet roof
- n° 5 open metal guard panels
- n° 1 HDPE sheet stairs with anti-slip recycled HDPE steps
- n° 3 shaped metal thrust bearings
- n° 1 metal thrust bearing
- n° 2 roto-molded PTE modular slides (H150)
- n° 2 2-rung metal backrests
- n° 1 4-rung metal backrest
- n° 1 metal «ARCO» climbing
- n° 1 rope climbing
- n° 1 rope bridge with metal side protections
- n° 5 HDPE sheet vertical climbings
- n° 15 HDPE sheet guard panels
- n° 5 HDPE sheet benches

PLAY PANELS

INSTALLATION



Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000