

# PRODUCT SHEET

REV 0.0 - IT202505

## 720 MIAMI




ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM  
ISO 9001:2015 CERTIFIED by  
EuCI European Certification Institute LTD  
Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM  
ISO 14001:2015 CERTIFIED by  
EuCI European Certification Institute LTD  
Certificate No.: GOTT2532E1801



|                                                                                     | CATALOG COLLECTION                  | LET'S PLAY TOGETHER   |
|-------------------------------------------------------------------------------------|-------------------------------------|-----------------------|
|  | <b>DIMENSIONS (L x W x H) in cm</b> | 1190 x 890 x 455 cm   |
|   | <b>IMPACT AREA</b>                  | 116,00 m <sup>2</sup> |
|  | <b>MAXIMUM CFH</b>                  | 125 cm                |
|  | <b>SUGGESTED AGE OF USE</b>         | 3+                    |
|  | <b>NUMBER OF USERS</b>              | 20                    |



# PRODUCT SHEET

REV 0.0 - IT202505

## 720 MIAMI



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM  
 ISO 9001:2015 CERTIFIED by  
**EuCI European Certification Institute LTD**  
 Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM  
 ISO 14001:2015 CERTIFIED by  
**EuCI European Certification Institute LTD**  
 Certificate No: GOTT2532E1801

### COMPOSITION

- n° 27 Ø120 mm hexagonal section aluminum posts
- n° 17 triangular powder-coated chequered aluminum decks
- n° 2 hexagonal roofs
- n° 2 HDPE sheet guard panels
- n° 4 closed metal guard panels
- n° 1 open roto-molded PTE guard panel
- n° 1 roto-molded PTE ramp
- n° 2 HDPE sheet climbings
- n° 3 HDPE sheet thrust bearing
- n° 1 «CORDE» bridge
- n° 2 access ramps
- n° 1 roto-molded PTE modular slide (H80)
- n° 1 roto-molded PTE tube modular slide (H125)
- n° 1 roto-molded PTE double modular slide (H110)
- n° 1 roto-molded PTE modular single slide (H125)
- HDPE sheet decorations

### PLAY PANELS



LUDIC PLAY PANEL  
x1



MUSICAL PLAY PANEL  
x1



EDUCATIONAL PLAY PANEL  
x1



EDUCATIONAL PLAY PANEL  
x1




LUDIC PLAY PANEL  
x1



LUDIC PLAY PANEL  
x1

### INSTALLATION



Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

| MATERIALE (mm)<br>MATERIAL (mm)                                                       | DESCRIZIONE (mm)<br>DESCRIPTION (mm)        | PROFONDITÀ MINIMA (mm) (b)<br>MINIMUM DEPTH (mm) (b) | ALTEZZA MASSIMA DI CADUTA (mm)<br>CRITICAL FALL HEIGHT (mm)      |
|---------------------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------|------------------------------------------------------------------|
| PRATO/TERRICCIO<br>LAWN/SOIL                                                          |                                             |                                                      | 1000 (d)                                                         |
| CORTECCIA<br>BARK                                                                     | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| TRUCIOLI DI LEGNO<br>WOOD CHIPS                                                       | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| SABBIA<br>SAND                                                                        | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| GHIAIA<br>GRAVEL                                                                      | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| PAVIMENTAZIONE IN GOMMA<br>RISPONDENTE A HIC<br>RUBBER SURFACING<br>RESPONDENT TO HIC |                                             |                                                      | SOTTOPOSTA A PROVE DI CADUTA<br>DEPENDENT ON CERTIFICATION TESTS |
|                                                                                       | SPESSORE/THICKNESS 30mm                     |                                                      | 1000                                                             |
|                                                                                       | SPESSORE/THICKNESS 40mm                     |                                                      | 1300                                                             |
|                                                                                       | SPESSORE/THICKNESS 45mm                     |                                                      | 1500                                                             |
|                                                                                       | SPESSORE/THICKNESS 60mm                     |                                                      | 2000                                                             |
|                                                                                       | SPESSORE/THICKNESS 70mm                     |                                                      | 2500                                                             |
|                                                                                       | SPESSORE/THICKNESS 90mm                     |                                                      | 3000                                                             |