

PRODUCT SHEET


REV 0.0 - IT202504

8881 T-1



SECURITY AREA


850




	CATALOG COLLECTION	PARTY LINE
	DIMENSIONS (L x W x H) in cm	755 x 505 x 470 cm
	IMPACT AREA	58,50 m²
	MAXIMUM CFH	200 cm
	SUGGESTED AGE OF USE	5+
	NUMBER OF USERS	12

COMPOSITION

- n° 11 70x70 mm octagonal section aluminium structural posts
- n° 2 recycled anti-slip HDPE decks
- HDPE sheet decorations
- n° 1 roto-molded PTE rotazionale guard panel
- n° 2 HDPE sheet and metal guard panels
- n° 1 metal climbing with handles
- n° 1 metal thrust bearing
- n° 1 roto-molded PTE modular slide (H190)
- n° 1 «RAMPA» bridge
- n° 1 HDPE sheet climbing with tube
- n° 2 rope climbing
- n° 2 HDPE sheet climbing
- n° 1 HDPE sheet bench

PLAY PANELS

**LUDIC PLAY PANEL
x1**
INSTALLATION


Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000