

PRODUCT SHEET

REV 0.0 - IT202504

6900 AL-HEIWA



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate No: GOTT2532E1801



SLIDING




CLIMBING




MEETING & ROLE PLAY



INTERACTIVE GAME




HANGING



SECURITY AREA

1850



CATALOG COLLECTION

PARTY LINE

DIMENSIONS (L x W x H) in cm

1510 x 940 x 500 cm

IMPACT AREA

156,00 m²

MAXIMUM CFH

270 cm

SUGGESTED AGE OF USE

3+

NUMBER OF USERS

50

PRODUCT SHEET

REV 0.0 - IT202504

6900 AL-HEIWA




ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
 ISO 9001:2015 CERTIFIED by
 EuCI European Certification Institute LTD
 Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
 ISO 14001:2015 CERTIFIED by
 EuCI European Certification Institute LTD
 Certificate No.: GOTT2532E1801

COMPOSITION

- n° 41 90x90 mm square section aluminum structural posts
- n° 12 powder-coated chequered aluminum footboards
- n° 3 roto-molded PTE four-pitched roofs
- n° 1 HDPE sheet roof
- n° 9 open metal guard panels
- n° 2 metal and HDPE sheet guard panels
- n° 3 double metal and HDPE sheet guard panels
- n° 7 HDPE sheet guard panels
- n° 9 HDPE sheet climbings
- n° 2 roto-molded PTE climbings
- n° 1 rope ladder and PTE rungs
- n° 1 shaped handrail
- n° 1 shaped handrail with handles
- n° 1 «ZIG-ZAG» perch
- n° 2 «ARCO» bridge
- n° 2 «RAMPA» bridge (25cm)
- n° 1 «RAMPA» bridge (40cm)
- n° 1 metal «ARCO» climbing
- n° 1 3-rung backrest
- n° 1 4-rung backrest
- n° 1 «JOLLY» net frame
- n° 2 HDPE sheet thrust bearing
- n° 1 roto-molded PTE double modular slide (H110)
- n° 1 roto-molded PTE modular slide (H120)
- n° 1 roto-molded PTE tube slide (H270)
- HDPE sheet decorations


PLAY PANELS




LUDIC PLAY PANEL
x1



MUSICAL PLAY PANEL
x1




MUSICAL PLAY PANEL
x1



EDUCATIONAL PLAY PANEL
x1

INSTALLATION



Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000