

# PRODUCT SHEET

REV 0.0 - IT202504

## 6990G ELLA



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM  
ISO 9001:2015 CERTIFIED by  
**EuCI European Certification Institute LTD**  
Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM  
ISO 14001:2015 CERTIFIED by  
**EuCI European Certification Institute LTD**  
Certificate No.: GOTT2532E1801



SLIDING




CLIMBING



SECURITY AREA

1200



800




|                                                                                     | CATALOG COLLECTION                  | FUN COLLECTION       |
|-------------------------------------------------------------------------------------|-------------------------------------|----------------------|
|  | <b>DIMENSIONS (L x W x H) in cm</b> | 495 x 855 x 580 cm   |
|   | <b>IMPACT AREA</b>                  | 74,00 m <sup>2</sup> |
|  | <b>MAXIMUM CFH</b>                  | 150 cm               |
|  | <b>SUGGESTED AGE OF USE</b>         | 5+                   |
|  | <b>NUMBER OF USERS</b>              | 35                   |

**COMPOSITION**

- n° 30 90x90 mm square section aluminum structural posts
- n° 18 anti-slip chequered aluminum decks
- n° 1 HDPE sheet roof
- n° 4 open metal guard panels
- n° 1 accessible stairs in HDPE sheet and anti-slip chequered aluminium steps
- n° 3 shaped metal thrust bearings
- n° 1 roto-molded PTE modular slides (H94)
- n° 1 roto-molded PTE modular slides (H150)
- n° 5 HDPE sheet climbings
- n° 1 3-rung metal backrest
- n° 1 metal «ARCO» climbing
- n° 1 net climbing
- n° 1 rope bridge with metal side protections
- n° 19 HDPE sheet guard panels
- n° 5 HDPE sheet benches

**PLAY PANELS**

**LUDIC PLAY PANEL**  
**x1**
**INSTALLATION**


Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

| MATERIALE (mm)<br>MATERIAL (mm)                                                       | DESCRIZIONE (mm)<br>DESCRIPTION (mm)        | PROFONDITÀ MINIMA (mm) (b)<br>MINIMUM DEPTH (mm) (b) | ALTEZZA MASSIMA DI CADUTA (mm)<br>CRITICAL FALL HEIGHT (mm)      |
|---------------------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------|------------------------------------------------------------------|
| PRATO/TERRICCIO<br>LAWN/SOIL                                                          |                                             |                                                      | 1000 (d)                                                         |
| CORTECCIA<br>BARK                                                                     | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| TRUCIOLI DI LEGNO<br>WOOD CHIPS                                                       | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| SABBIA<br>SAND                                                                        | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| GHIAIA<br>GRAVEL                                                                      | PEZZATURA DA 20 A 80<br>20 TO 80 GRAIN SIZE | 200<br>300                                           | 2000<br>3000                                                     |
| PAVIMENTAZIONE IN GOMMA<br>RISPONDENTE A HIC<br>RUBBER SURFACING<br>RESPONDENT TO HIC |                                             |                                                      | SOTTOPOSTA A PROVE DI CADUTA<br>DEPENDENT ON CERTIFICATION TESTS |
|                                                                                       | SPESSORE/THICKNESS 30mm                     |                                                      | 1000                                                             |
|                                                                                       | SPESSORE/THICKNESS 40mm                     |                                                      | 1300                                                             |
|                                                                                       | SPESSORE/THICKNESS 45mm                     |                                                      | 1500                                                             |
|                                                                                       | SPESSORE/THICKNESS 60mm                     |                                                      | 2000                                                             |
|                                                                                       | SPESSORE/THICKNESS 70mm                     |                                                      | 2500                                                             |
|                                                                                       | SPESSORE/THICKNESS 90mm                     |                                                      | 3000                                                             |