

PRODUCT SHEET

REV 2.0 - IT202509

H170M CANYON MAXI



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate N.: GOTT2532Q1902


ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate No.: GOTT2532E1801



SECURITY AREA

1450

	CATALOG COLLECTION	LET'S PLAY TOGETHER
	DIMENSIONS (L x W x H) in cm	1150 x 630 x 315 cm
	IMPACT AREA	88,50 m ²
	MAXIMUM CFH	113 cm
	SUGGESTED AGE OF USE	3+
	NUMBER OF USERS	28






COMPOSITION

- n°28 aluminium poles 90x90mm section
- n°5 aluminium decks
- n°3 HDPE sheet roofs
- n°2 open metal guardpanels
- n°2 metal handhold
- n°2 access ramps
- n°3 modular slides
- n°1 HDPE sheet climbing
- n°1 rotating mold PTE climbing
- n°1 slope bridge with rope
- n°1 ramp bridge with HDPE sidepanels
- n°1 HDPE sheet handhold
- HDPE sheet decorations

PLAY PANELS

MUSICAL PLAY PANEL
x1

LUDIC PLAY PANEL
x4

INSTALLATION


Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000