

SCHEDA PRODOTTO
REV 0.0 - IT202504
475 FEDORA



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate No.: GOTT2532E1801



INCONTRO E
GIOCO SIMBOLICO



GIOCO INTERATTIVO




SCIVOLARE



ARRAMPICARE



AREA DI SICUREZZA



	COLLEZIONE	PLAYGROUND ESSENTIALS
	DIMENSIONI (L x P x H)	315 x 230 x 210 cm
	AREA D'IMPATTO	25,50 m ²
	ALTEZZA CRITICA DI CADUTA	90 cm
	ETÀ D'USO CONSIGLIATA	3+
	NUMERO UTILIZZATORI	10

SCHEDA PRODOTTO

REV 0.0 - IT202504

475 FEDORA



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
 ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
 Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
 ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
 Certificate No: GOTT2532E1801


COMPOSIZIONE

- struttura portante in acciaio inox verniciata a polvere
- n° 3 pedane in HDPE antiscivolo riciclato
- n° 1 scala con fianchi in lastra HDPE e gradini in lastra HDPE riciclato antiscivolo
- n° 2 fianchi in lastra HDPE
- n° 1 rampa inclinata in lastra HDPE
- n° 2 arrampicate in lastra HDPE
- n° 1 reggispinta in lastra HDPE
- n° 1 scivolo modulare in PTE rotazionale (H90)
- decori in lastra HDPE


PANNELLI GIOCO



PANNELLO LUDICO
x1



PANNELLO LUDICO
x1



PANNELLO LUDICO
x1



PANNELLO EDUCATIVO
x1

Realizzare un idoneo fondo antitrauma in funzione dell'altezza critica di caduta. Manutenzione periodica obbligatoria come da piano consegnato al cliente.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000