

PRODUCT SHEET


REV 0.0 - IT202504

6003 MANIERO



ORGANIZATION WITH QUALITY MANAGEMENT SYSTEM
ISO 9001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate N.: GOTT2532Q1902

ORGANIZATION WITH ENVIRONMENTAL MANAGEMENT SYSTEM
ISO 14001:2015 CERTIFIED by
EuCI European Certification Institute LTD
Certificate No: GOTT2532E1801




SLIDING



CLIMBING




CRAWLING



WALK/BALANCE



INTERACTIVE GAME



SECURITY AREA

1000

950

64,00m²

	CATALOG COLLECTION	FUN COLLECTION
	DIMENSIONS (L x W x H) in cm	625 x 677 x 306 cm
	IMPACT AREA	64,00 m ²
	MAXIMUM CFH	200 cm
	SUGGESTED AGE OF USE	5+
	NUMBER OF USERS	35

PRODUCT SHEET

REV 0.0 - IT202504


6003 MANIERO

COMPOSITION


- n° 22 90x90 mm square section aluminum structural posts
- n° 6 decks with powder-coated metal frame and aluminium slats
- n° 5 open metal guard panels
- n° 5 HDPE sheet guard panels
- n° 1 roto-molded PTE climbing
- n° 1 «ZIG-ZAG» perch
- n° 1 metal tubular slide
- n° 1 roto-molded PTE modular slide (H125)
- n° 1 HDPE sheet thrust bearing
- n° 2 roto-molded PTE tunnels
- n° 1 «WOBBLE» bridge
- n° 1 «CORDE» bridge
- n° 1 three-rung backrest
- n° 1 two-rung backrest
- n° 1 horizontal backrest
- HDPE decorations

PLAY PANELS

INSTALLATION



Where there is an aluminum pole, the plinth must be created directly on it.



If there is already an adequate fund in CLS the game can be supplied with special brackets for fixing to the ground (option applicable only with confirmation of feasibility).

Make a proper security surface according to CFH. Periodic maintenance is mandatory, following manual supplied to customer.

MATERIALE (mm) MATERIAL (mm)	DESCRIZIONE (mm) DESCRIPTION (mm)	PROFONDITÀ MINIMA (mm) (b) MINIMUM DEPTH (mm) (b)	ALTEZZA MASSIMA DI CADUTA (mm) CRITICAL FALL HEIGHT (mm)
PRATO/TERRICCIO LAWN/SOIL			1000 (d)
CORTECCIA BARK	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
TRUCIOLI DI LEGNO WOOD CHIPS	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
SABBIA SAND	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
GHIAIA GRAVEL	PEZZATURA DA 20 A 80 20 TO 80 GRAIN SIZE	200 300	2000 3000
PAVIMENTAZIONE IN GOMMA RISPONDENTE A HIC RUBBER SURFACING RESPONDENT TO HIC			SOTTOPOSTA A PROVE DI CADUTA DEPENDENT ON CERTIFICATION TESTS
	SPESSORE/THICKNESS 30mm		1000
	SPESSORE/THICKNESS 40mm		1300
	SPESSORE/THICKNESS 45mm		1500
	SPESSORE/THICKNESS 60mm		2000
	SPESSORE/THICKNESS 70mm		2500
	SPESSORE/THICKNESS 90mm		3000